

VISSER dual conveyor type DTV

VISSER
HANDLING EQUIPMENT



The VISSER telescopic dual conveyor type DTV is designed for transporting your product at high capacities. The product and user-friendly design ensures you of work pleasure and convenience.

As standard, VISSER provides the dual conveyor with electric retraction and extension with 2 chains for a longer lifespan.

All our duo belts are equipped with a hand pump with cylinder for height adjustment. Due to the high discharge, it is possible to fill a box filler directly with the 2nd belt.

The belt has a trough shape with moving sides that prevent product damage. The moving sides ensure a high capacity and give you the possibility to read your product at the belt.

The VISSER dual conveyor DTV is available in 70 and 80 cm width.



Optional: hydraulic steering
/drive



Strong tandem
wheels



Heavy duty energy chain



Electric in- and out

VISSER HANDLING EQUIPMENT

Technische specificaties VISSER duobanden DTV

Capacity:	Ca. 75-100 t/hr.
Standard:	Electrical retraction and extension with roller chain. Smooth rubber belt, rollers supported and sliding side walls. Height adjustment with spindles (standard, zero price) First belt 2 speeds, second belt 1 speed Smooth rubber belt Scrapers on the return rollers Fixed kink on the exit side of the second belt Control box, with thermal protection With phase sequence relay and reversing switch
Optional:	Drawbar Forklift sleeves Bigger wheels Power cables through the frame Frequency inverter(s) SLC of VLC Line Control Steering rod Round rubber intake funnel, adjustable Coupled spindles height adjustment Hydraulic drive wheels with steering and height adjustment Work lights for reading at the belt Coupling discharge side for store loader

Type	DTV 13/8	DTV 15/9	DTV 17/10	DTV 19/11
Extended length	13,2 m.	15,2 m.	17,2 m.	19,2 m.
Retracted length	7,0 m.	9,0 m.	11,0 m.	13,0 m.
Width 70 cm possible	o	o	o	o
Width 80 cm possible	o	o	o	o
Beltspeed first belt	27/54 m/min.	27/54 m/min.	27/54 m/min.	27/54 m/min.
Beltspeed second belt	54 m/min.	54 m/min.	54 m/min.	54 m/min.
Width frame first belt	1,65 m.	1,65 m.	1,65 m.	1,65 m.
Width frame second belt	1,75 m.	1,75 m.	1,75 m.	1,75 m.
Highest output height	2,3 m.	2,3 m.	2,3 m.	2,3 m.





VISSER
HANDLING EQUIPMENT

De Marne 1
8701 PV Bolsward

Tel: +31 (0)85 732 54 00
@: info@visserbolsward.com

www.visserbolsward.com